

Teison Smart mini

TS-EVC07-003(S)

TS-EVC11-003(S)

TS-EVC22-003(S)







TABLE OF CONTENTS

	Product features 02
Z Q	Parameter 04
S	OCPP function list 05
Start to charge (APP) 09	Size and packaging 06
Earth rod solution 12	Product installation 07
Fault handling 14	

Teison Profile | 15


Factory history | 16

Product overview | 01

Product overview

Smart charger, Small size, Stylish design

Easy control via mobile APP, always being the most reliable and safe home charger.



* This product does not include incoming cables when leaving the factory , and this picture is only for display



Product features



Solid design wallbox

Meet IP65 & IK10 standard by lab test excellent water protection.



Indicator light

Showing real time charging status



Smart mini

Teison smart components highly integrated in a 228.5x228.5x100 mm Size mini body



TUV certified

All parts passed CE Certificates, and tested by TUV.



Smart charging

The smartphone App can realize the remote control and organize. Integration with OCPP 1.6 J-SON system.

Real Smart

- Control your smart wallbox through Teison App by Bluetooth, WIFI and 4G
- Developed based on OCPP 1.6 J-SON
- Automatic identification
- Max charging Current adjustable
- Remote reach out of every charging process
- Charging records in Cloud
- Scheduled charging to save on your electricity bill
- OTA for new features

Highest safety

- PCV 0 housing with 2.0~3.0 mm thick exudes robustness and protects inside components from external influences.
- The housing is made from materials specially developed fortop heat dissipation and with flame retardant coating.
- Completely meets all requirements of the CE applicable standards.
- AC + DC faults detection
- Real-time monitoring for heat and all instabilities during charging process

Parameter

Specification				
Model	TS-EVC07-003(S)	TS-EVC11-003(S)	TS-EVC22-003(S)	
Electrical Properties				
Voltage	230V AC ±10%	380V AC ±10%	380V AC ±10%	
Output Current	32A	16A	32A	
Frequency	50/60Hz	50/60Hz	50/60Hz	
Output Power	7kw	11kw	22kw	
Residual current protection	TYPE A(30mA AC)	1		
Design				
Charging Outlet	4.5M charging cable with	type1/2 plug or type2 sock	et	
Power incoming line	0.7M			
Housing Material	PCV0 for outdoor			
Installation Method	Wall-mount/Floor-stand			
Communication Protocol	OCPP 1.6 J-SON	OCPP 1.6 J-SON		
Safety Standard	EN IEC 61851-21-2:2021; EN IEC 61000-6-1:2019; EN IEC 61000-6-2:2019; EN IEC 61000-6-3:2021; EN IEC 61851-1:2019; EN IEC 61000-6-4:2019; ETSI EN 300 328 V2.2.2:2019; ETSI EN 300 330 V2.1.1:2017; ETSI EN 301 489-1 V2.2.3:2019; ETSI EN 301 489-3 V2.1.1:2019; ETSI EN 301 489-17 V3.2.4:2020; EN IEC 62311:2020, IEC 61851-1:2017			
Warranty	2 years			
Environmental Performance				
Protection Level	IP65			
Working Altitude	<2000M			
Application Site	Indoor/Outdoor			
Working temperature	-30°C~+50°C			
Working humidity	5%~95%, No condensation			
Atmospheric pressure	80kPa~101kPa			
Functionality				
Network Gateway	Bluetooth and WIFI as default			
Mobile APP (los and Android supported) functions under Bluetooth	Scheduled charging Start charging Stop charging Current adjustment (memorable) plug and play charging switch on APP Charging status shown on APP			
Added APP functions under WIFI / 4G	Charging records shown on mobile APP、view and update the PIN code、firmware updating function(OTA)、multiple wallbox control			
Packing Details				
Product Size	228.5*228.5*100mm	228.5*228.5*100mm	228.5*228.5*100mm	
Product Weight	4.4KG	5.2KG	5.4KG	
OptionalConfig				
Residual current protection	Residual current protection TYPE B (AC 30MA + DC 6 MA) as optional			
Network Gateway	4G as optional			
O-PEN detection	as optional			
RFID	as optional (with 3 RFID cards)			
load balance	RS485 meter/CT-Clamp as optional			
Installation method	Stand-pile Stand-pile			

OCPP function list

1 Authorize √ 2 BootNotification √ 3 ChangeAvailability √ 4 ChangeConfiguration √ 5 ClearCache √ 6 DataTransfer P 7 GetConfiguration √ 8 Heartbeat √ 9 MeterValues √ 10 RemoteStartTransaction √ 11 RemoteStopTransaction √ 12 Reset √ 13 StartTransaction √ 14 StatusNotification √ 15 StopTransaction √ 16 UnlockConnector √ 17 TriggerMessage √ 18 GetDiagnostics √ 19 DiagnosticsStatusNotification √ 20 FirmwareStatusNotification √
3 ChangeAvailability √ 4 ChangeConfiguration √ 5 ClearCache √ 6 DataTransfer P 7 GetConfiguration √ 8 Heartbeat √ 9 MeterValues √ 10 RemoteStartTransaction √ 11 RemoteStopTransaction √ 12 Reset √ 13 StartTransaction √ 14 StatusNotification √ 15 StopTransaction √ 16 UnlockConnector √ 17 TriggerMessage √ 18 GetDiagnostics √ 19 DiagnosticsStatusNotification √
4 ChangeConfiguration √ 5 ClearCache √ 6 DataTransfer P 7 GetConfiguration √ 8 Heartbeat √ 9 MeterValues √ 10 RemoteStartTransaction √ 11 RemoteStopTransaction √ 12 Reset √ 13 StartTransaction √ 14 StatusNotification √ 15 StopTransaction √ 16 UnlockConnector √ 17 TriggerMessage √ 18 GetDiagnostics √ 19 DiagnosticsStatusNotification √
5 ClearCache √ 6 DataTransfer P 7 GetConfiguration √ 8 Heartbeat √ 9 MeterValues √ 10 RemoteStartTransaction √ 11 RemoteStopTransaction √ 12 Reset √ 13 StartTransaction √ 14 StatusNotification √ 15 StopTransaction √ 16 UnlockConnector √ 17 TriggerMessage √ 18 GetDiagnostics √ 19 DiagnosticsStatusNotification √
6 DataTransfer P 7 GetConfiguration √ 8 Heartbeat √ 9 MeterValues √ 10 RemoteStartTransaction √ 11 RemoteStopTransaction √ 12 Reset √ 13 StartTransaction √ 14 StatusNotification √ 15 StopTransaction √ 16 UnlockConnector √ 17 TriggerMessage √ 18 GetDiagnostics √ 19 DiagnosticsStatusNotification √
7 GetConfiguration √ 8 Heartbeat √ 9 MeterValues √ 10 RemoteStartTransaction √ 11 RemoteStopTransaction √ 12 Reset √ 13 StartTransaction √ 14 StatusNotification √ 15 StopTransaction √ 16 UnlockConnector √ 17 TriggerMessage √ 18 GetDiagnostics √ 19 DiagnosticsStatusNotification √
8 Heartbeat √ 9 MeterValues √ 10 RemoteStartTransaction √ 11 RemoteStopTransaction √ 12 Reset √ 13 StartTransaction √ 14 StatusNotification √ 15 StopTransaction √ 16 UnlockConnector √ 17 TriggerMessage √ 18 GetDiagnostics √ 19 DiagnosticsStatusNotification √
9 MeterValues √ 10 RemoteStartTransaction √ 11 RemoteStopTransaction √ 12 Reset √ 13 StartTransaction √ 14 StatusNotification √ 15 StopTransaction √ 16 UnlockConnector √ 17 TriggerMessage √ 18 GetDiagnostics √ 19 DiagnosticsStatusNotification √
10 RemoteStartTransaction √ 11 RemoteStopTransaction √ 12 Reset √ 13 StartTransaction √ 14 StatusNotification √ 15 StopTransaction √ 16 UnlockConnector √ 17 TriggerMessage √ 18 GetDiagnostics √ 19 DiagnosticsStatusNotification √
11 RemoteStopTransaction √ 12 Reset √ 13 StartTransaction √ 14 StatusNotification √ 15 StopTransaction √ 16 UnlockConnector √ 17 TriggerMessage √ 18 GetDiagnostics √ 19 DiagnosticsStatusNotification √
12 Reset √ 13 StartTransaction √ 14 StatusNotification √ 15 StopTransaction √ 16 UnlockConnector √ 17 TriggerMessage √ 18 GetDiagnostics √ 19 DiagnosticsStatusNotification √
13 StartTransaction 14 StatusNotification 15 StopTransaction 16 UnlockConnector 17 TriggerMessage 18 GetDiagnostics 19 DiagnosticsStatusNotification ✓
14 StatusNotification √ 15 StopTransaction √ 16 UnlockConnector √ 17 TriggerMessage √ 18 GetDiagnostics √ 19 DiagnosticsStatusNotification √
15 StopTransaction 16 UnlockConnector 17 TriggerMessage 18 GetDiagnostics √ 19 DiagnosticsStatusNotification √
16 UnlockConnector √ 17 TriggerMessage √ 18 GetDiagnostics √ 19 DiagnosticsStatusNotification √
17 TriggerMessage √ 18 GetDiagnostics √ 19 DiagnosticsStatusNotification √
18 GetDiagnostics √ 19 DiagnosticsStatusNotification √
19 DiagnosticsStatusNotification √
20 FirmwareStatusNotification √
21 UpdateFirmware √
22 GetLocalListVersion √
23 SendLocalList √
24 ReserveNow √
25 CancelReservation √
26 ClearChargingProfile √
27 GetCompositeSchedule P
28 SetChargingProfile √

^{√ –} Supported

P – Need to be combined with the back-end

Product size and packaging

Product size: 228.5*228.5*100mm


Product net weight: 3kg

Product gross weight: 3.5kg




Package:

550*233*146mm




Product installation


Installation method 1




1. Use a drill to make mounting holes in suitable locations on the wall.




2. Tap the expansion bolts into the mounting holes.




3. Mounting the wallbox back plate on the wall.



4. Place the wallbox in from the top down and fix it to the back plate



5. Organise and secure the incoming cables of the wallbox.




6. Remove the protective film from the front panel to start using the product.

Installation method 2






1.Remove the two screws at the bottom of the cover plate, then push down and remove it from the wallbox.




2.Remove the 7 screws around the internal panel and take the panel down.




3. Use a drill to make mounting holes in suitable locations on the wall.



4. Tap the expansion bolts into the mounting holes.



5.Mounting the disassembled back cover on the wall




6.Install the removed front panel back in order.


Wiring Diagram



Single-Phase



or



Three-Phase


Start to charge (APP)

App need to be given the authority to use the GPS and Bluetooth, at the first to use.


> My Teison can't use network Access location info Deny Once Allow only while using the app

Home(HOME):Support Smart Mini OCPP charger for home user, with Bluetooth and Remote Control Commercial:For commercial use in public

area, realize charging and operation of the charging stations.



Register your information and login



Moile App operation-Connection


1.Local Devices list, press "Use immediately" enter into the user page. 2.Online Devices list. showing all the online chargers bonded by user. Parameters: Device name. Serial No., Status, type etc. To press "Use immediately" enter into online charger User interface.

3. Press "+Add device" for web configuration. 4. Devices selected area. to find out the correct charging station.



Mobile App operation- Connection:

- 1. Select: "Use immediately" to use local device.
- 2. Click the "..." button upper right side.
- 3. Click "Config Network"
- 4. By Wi-fi or 4G connection
- 4.1 ocpp1.6 If choose Wifi(Only supports 2.4G wifi), input your wifi password.
- 4.2 If choose 4G, input 4G network APN configuration.
- 5. Network Configuration will finish in 30seconds.(If you use the ocpp platform by the third-party, it will show success by step 2, have to confirm it by your platform)
- 6. Config. success. To name your online charger.
- 7. Back to homepage, the device after success configuring network will show in the list, (if not in the list, pull down to refresh the page).




Moile App operation- Pin Code

- 1. You can check your PIN code by local device management (press "..." on your home page).
- 2. Copy PIN code or Refresh PIN code
- 3. Pin Code can be shared to others for the usage of charger






o-PEN: Earth rod solution




In line with BS 7671: 2018: Amendment 2: 2020 Regulation 722.411.4.1(iv) Protection against electric shock in a single-phase installation is provided by a device which electrically disconnects the vehicle from the live conductors of the supply and from protective earth in accordance with regulation 543.3.3.101 (ii) within 5 s in the event of the utilisation voltage at the charging point, between the line and neutral conductors, being greater than 253 V rms or less than 207 V rms. The device shall provide isolation and be selected in accordance with Table 537.4. Equivalent means of functionality could be included within the charging equipment. Closing or resetting of the device shall be possible only if the voltage between line and neutral conductors is in the range 207 to 253 V rms.

Preconditions: Some use scenarios cannot provide a good ground (PE) for the charging box, and most cars themselves do not provide a conductive path to the ground, and the car body is generally connected to the PE:


1. Under normal circumstances, the source end of the N line is well grounded, the car is insulated from the ground, and no circuit loop is formed. It is safe at this time.




2. When the charging box plug is connected and the human body contacts the car body, it provides a conductive circuit between the car body and the ground. The human body is equivalent to a large resistance and provides a conductive circuit. At this time, there is already a risk. If the incoming line N of the charging pile is well grounded at this time, since Rb is much smaller than the equivalent resistance of the human body, the current flowing through the human body is very small and the human body does not perceive it. People are safe.



3. When the N line of the charging box is abnormally disconnected or presents a large impedance, the circuit loop will be conducted through the human body to the earth, which will cause the human body to get an electric shock. At this time, the usual L and N leakage protection will be invalid, and new methods are needed. protect.



4. Measure 1: V1+V2=230V, check V1, when V1<170V, disconnect all paths within 1S to avoid the risk of human electric shock.



Fault handling

Red light flash times	Condition	LED Status
1	Electric leakage	
2	Over-voltage (Input voltage is more than 280v)	
3	Under-voltage (Input voltage is less than 80V)	
4	Over-current (Output current is more than the rated value by 10%)	
5	Over-temperature (Temperature is more than 95°C)	
6	Electric leakage self-testing abnormal	Below indicator light flash slowly
7	/	
8	CP pilot abnormal	
9	Relay abnormal	
10	Assist processor abnormal	
11	System 12v abnormal	
12	System -12v abnormal	



Teison Profile

Teison Energy Technology Co., Ltd. is a high-tech enterprise dedicated to new energy products. With its industry-leading R&D and design team, it has advanced automobile charging technology and products that can solve energy management, load balancing, commercial operations, data transmission, remote upgrading, and operation and maintenance management in various application scenarios. It provides users with an integrated "Solar-storage-charge" solution.

Teison's products comply with national, European, American, and Japanese standards, including household intelligent charging series and high-power fast charging and supercharging direct current series for commercial operations that are available in AC and DC, mobile, and portable models. They have been certified by the OCPP1.6J certification of the OCA alliance, Germany's TUV Rheinland for CE, CB, WEEE, UKCA, TR25, and AZE certifications, and the national grid 16949 certification.

As a smart charging expert, Teison's products are sold worldwide. It has established more than 100 sales outlets in over 40 countries, and has set up subsidiaries, overseas warehouses, and after-sales service departments in Europe, the Middle East, South America, and Southeast Asia to provide users with efficient and fast technical support.

As a safety charging expert, Teison insists on putting safety first, and product quality is the essential guarantee of safety. It creates aesthetically designed, high-quality, and safety-friendly charging scenes for users, and together with Teison's technology, lets users enjoy a better life.

Factory history

