

TECHNICAL DATA

SHARP 10 BATTERY CHARGERS

Type MAINS DATA (50/60HZ) Output Voltage [V] Output Current [A] Number of phases Rated Voltage range [V]	924114 SHARP 10 12V/10A
Type MAINS DATA (50/60HZ) Output Voltage [V] Output Current [A] Number of phases Rated Voltage range [V]	
MAINS DATA (50/60HZ) Output Voltage [V] Output Current [A] Number of phases Rated Voltage range [V]	12V/10A
Output Voltage [V] Output Current [A] Number of phases Rated Voltage range [V]	
Output Current [A] Number of phases Rated Voltage range [V]	
Number of phases Rated Voltage range [V]	12
Rated Voltage range [V]	10
	1
Current at nominal voltage [A]	208-240
	0,8
Recommended supply fuse [A]	10
Supply cable area	3x1,0
Supply cable length [m]	2
Typical Supply Connector	16A Schuko
Output cable cross-section	2x2,5
BATTERY CONNECTION	
Output cable cross-section	2x2,5
Output cable terminals (in unit)	-
Output cable length [m]	1,5
Typical Output connector	User defined
Output Voltage [V]	12
ELECTRIC DATA	
Standby Power Consumption [W]	
Power Consumption [W]	1
Apparent Power Consumption [VA]	1

Power Factor	0,9
Inrush current, do not tripp fuse of class [A]	Negligible
Output Ripple	4
Efficiency (at rated power and no cables) [%]	87
PROPERTIES	
Ingress protection	IP65
Ambient temperature range (at full output power) [deg C]	-25 to +30
Ambient max temp (with reduced output power) [deg C]	55
Cooling: 1=Fan, 2= Convection	Passive
Short Circuit Protection	Yes
Wrong Polarity Protection	Yes
Cabinet Type	P1
Certifications	
НМІ	LED
HMI Language	-
Reporting	No
Radio Communication	No
Charging Curve Set	Customer demand
I/O-cards	No
CE	Yes
UL	No
CHARGING TIMES	
6 Hours cap.ah/5h	31
8 Hours cap.ah/5h	41
10 Hours cap.ah/5h	55
12 Hours cap.ah/5h	66
CHARGER DIMENSIONS	
Weight excl. cables [kg]	
Weight incl. cables [kg]	
Outer Dimensions Height [mm]	192

Outer Dimensions Width [mm]	98
Outer Dimensions Depth [mm]	48
Min Spacing Required	150
SHIPPING DIMENSIONS	
Shipping Weight [kg]	2
Box Height [mm]	193
Box Width [mm]	99
Box Depth [mm]	48
CHARGING	
Charging Ionic	LK Sharp 10
Charging Standard	LK Sharp 10
Charging Gel	LK Sharp 10 (GEL and AGM)
Charging Li-lon	0
Charging AGM	LK Sharp 10 (GEL and AGM)
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No