

TECHNICAL DATA

SHARP 10 BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

| | |
|-------------|----------|
| Part number | 924119 |
| Model | SHARP 10 |
| Type | 12V/17A |

MAINS DATA (50/60HZ)

| | |
|--------------------------------|------------|
| Output Voltage [V] | 12 |
| Output Current [A] | 17 |
| Number of phases | 1 |
| Rated Voltage range [V] | 208-240 |
| Current at nominal voltage [A] | 1,4 |
| Recommended supply fuse [A] | 10 |
| Supply cable area | 3x1,0 |
| Supply cable length [m] | 2 |
| Typical Supply Connector | 16A Schuko |
| Output cable cross-section | 2x2,5 |

BATTERY CONNECTION

| | |
|----------------------------------|--------------|
| Output cable cross-section | 2x2,5 |
| Output cable terminals (in unit) | - |
| Output cable length [m] | 1,5 |
| Typical Output connector | User defined |
| Output Voltage [V] | 12 |

ELECTRIC DATA

| | |
|---------------------------------|-----|
| Standby Power Consumption [W] | 1 |
| Power Consumption [W] | 281 |
| Apparent Power Consumption [VA] | 313 |

| | |
|--|------------|
| Power Factor | 0,9 |
| Inrush current, do not tripp fuse of class [A] | Negligible |
| Output Ripple | <1 |
| Efficiency (at rated power and no cables) [%] | 87 |

PROPERTIES

| | |
|--|-----------------|
| Ingress protection | IP65 |
| Ambient temperature range (at full output power) [deg C] | -25 to +30 |
| Ambient max temp (with reduced output power) [deg C] | 55 |
| Cooling: 1=Fan, 2= Convection | Passive |
| Short Circuit Protection | Yes |
| Wrong Polarity Protection | Yes |
| Cabinet Type | P1 |
| Certifications | |
| HMI | LED |
| HMI Language | - |
| Reporting | No |
| Radio Communication | No |
| Charging Curve Set | Customer demand |
| I/O-cards | No |
| CE | Yes |
| UL | No |

CHARGING TIMES

| | |
|--------------------|-----|
| 6 Hours cap.ah/5h | 52 |
| 8 Hours cap.ah/5h | 69 |
| 10 Hours cap.ah/5h | 93 |
| 12 Hours cap.ah/5h | 112 |

CHARGER DIMENSIONS

| | |
|------------------------------|-----|
| Weight excl. cables [kg] | |
| Weight incl. cables [kg] | |
| Outer Dimensions Height [mm] | 192 |

| | |
|-----------------------------|-----|
| Outer Dimensions Width [mm] | 98 |
| Outer Dimensions Depth [mm] | 48 |
| Min Spacing Required | 150 |

SHIPPING DIMENSIONS

| | |
|----------------------|-----|
| Shipping Weight [kg] | 2 |
| Box Height [mm] | 193 |
| Box Width [mm] | 99 |
| Box Depth [mm] | 48 |

CHARGING

| | |
|---------------------|---------------------------|
| Charging Ionic | LK Sharp 10 |
| Charging Standard | LK Sharp 10 |
| Charging Gel | LK Sharp 10 (GEL and AGM) |
| Charging Li-Ion | 0 |
| Charging AGM | LK Sharp 10 (GEL and AGM) |
| Moisture Resistance | No |
| Dusty Environment | No |
| Outdoor use | No |
| Cold store | No |
| Tropical | No |

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.