

TECHNICAL DATA

SHARP 20 BATTERY CHARGERS

| STATED DATA ACCORDING TO MICRO | POWER STANDARD |
|----------------------------------|----------------|
| Part number | 924419 |
| Model | SHARP 20 |
| Туре | 48V/15A |
| MAINS DATA (50/60HZ) | |
| Output Voltage [V] | 48 |
| Output Current [A] | 15 |
| Number of phases | 1 |
| Rated Voltage range [V] | 220-240 |
| Current at nominal voltage [A] | 4,3 |
| Recommended supply fuse [A] | 10 |
| Supply cable area | 3x1,5 |
| Supply cable length [m] | 2,5 |
| Typical Supply Connector | 10A Schuko |
| Output cable cross-section | 2x6 |
| BATTERY CONNECTION | |
| Output cable cross-section | 2x6 |
| Output cable terminals (in unit) | Terminal |
| Output cable length [m] | 2 |
| Typical Output connector | User defined |
| Output Voltage [V] | 48 |
| ELECTRIC DATA | |
| Standby Power Consumption [W] | <5 |
| Power Consumption [W] | 976 |
| Apparent Power Consumption [VA] | 986 |

Printout date: 2023-08-04

| Power Factor | 0,99 |
|--|------------------|
| Inrush current, do not tripp fuse of class [A] | Negligible |
| Output Ripple | <1 |
| Efficiency (at rated power and no cables) [%] | 89 |
| PROPERTIES | |
| Ingress protection | IP20 |
| Ambient temperature range (at full output power) [deg C] | -5 to +40 |
| Ambient max temp (with reduced output power) [deg C] | 50 |
| Cooling: 1=Fan, 2= Convection | Fan |
| Short Circuit Protection | Yes |
| Wrong Polarity Protection | Electronic |
| Cabinet Type | P4 |
| Certifications | |
| НМІ | LED |
| HMI Language | - |
| Reporting | No |
| Radio Communication | No |
| Charging Curve Set | 10-04,06 & 20-09 |
| I/O-cards | No |
| CE | Yes |
| UL | No |
| CHARGING TIMES | |
| 6 Hours cap.ah/5h | 76 |
| 8 Hours cap.ah/5h | 115 |
| 10 Hours cap.ah/5h | 157 |
| 12 Hours cap.ah/5h | 199 |
| CHARGER DIMENSIONS | |
| Weight excl. cables [kg] | |
| Weight incl. cables [kg] | |
| Outer Dimensions Height [mm] | 243 |

| Outer Dimensions Width [mm] | 112 |
|-----------------------------|---|
| Outer Dimensions Depth [mm] | 74 |
| Min Spacing Required | 150 |
| SHIPPING DIMENSIONS | |
| Shipping Weight [kg] | 2 |
| Box Height [mm] | 310 |
| Box Width [mm] | 200 |
| Box Depth [mm] | 140 |
| CHARGING | |
| Charging Ionic | LK10-04 Chemical Acid Circulation (Ionic) |
| Charging Standard | LK10-06 Standard Curve |
| Charging Gel | LK20-09 |
| Charging Li-lon | 0 |
| Charging AGM | LK20-09 |
| Moisture Resistance | No |
| Dusty Environment | No |
| Outdoor use | No |
| Cold store | No |
| Tropical | No |