

## **TECHNICAL DATA**

## **SHARP 30 BATTERY CHARGERS**

STATED DATA ACCORDING TO MICROPOWE	ER STANDARD
Part number	SC2420
Model	Sharp 30
Туре	24V/100A
MAINS DATA (50/60HZ)	
Output Voltage [V]	24
Output Current [A]	100
Number of phases	1
Rated Voltage range [V]	220-240
Current at nominal voltage [A]	13,9
Recommended supply fuse [A]	16
Supply cable area	3x1,5
Supply cable length [m]	2,5
Typical Supply Connector	16A Schuko
Output cable cross-section	2x25
BATTERY CONNECTION	
Output cable cross-section	2x25
Output cable terminals (in unit)	-
Output cable length [m]	3
Typical Output connector	User defined
Output Voltage [V]	24
ELECTRIC DATA	
Standby Power Consumption [W]	<5
Power Consumption [W]	3151
Apparent Power Consumption [VA]	3182

Printout date: 2023-08-03

Power Factor	0,99
Inrush current, do not tripp fuse of class [A]	<30
Output Ripple	<1
Efficiency (at rated power and no cables) [%]	93
PROPERTIES	
Ingress protection	IP54 (IP66 optional)
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling: 1=Fan, 2= Convection	Fan
Short Circuit Protection	Yes
Wrong Polarity Protection	Fuse
Cabinet Type	\$12
Certifications	
НМІ	LED
HMI Language	-
Reporting	No
Radio Communication	No
Charging Curve Set	10-05,06,18 & 20-09 & 23-03
I/O-cards	No
CE	Yes
UL	No
CHARGING TIMES	
6 Hours cap.ah/5h	574
8 Hours cap.ah/5h	833
10 Hours cap.ah/5h	1112
12 Hours cap.ah/5h	1375
CHARGER DIMENSIONS	
Weight excl. cables [kg]	
Weight incl. cables [kg]	
Outer Dimensions Height [mm]	407

Outer Dimensions Width [mm]	235
Outer Dimensions Depth [mm]	78
Min Spacing Required	100
SHIPPING DIMENSIONS	
Shipping Weight [kg]	9
Box Height [mm]	600
Box Width [mm]	265
Box Depth [mm]	165
CHARGING	
Charging Ionic	LK10-18 Ionic mixture
Charging Standard	LK10-06 Standard Curve
Charging Gel	LK20-09
Charging Li-lon	0
Charging AGM	LK20-09
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No