

TECHNICAL DATA

SHARP 80 48V/100A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

| | |
|-------------|----------|
| Family | SHARP 80 |
| DC Rating | 48V/100A |
| Part number | SM4429 |
| Model code | 1AB6010 |
| Part status | Released |

SUPPLY

| | |
|---|-----------------------|
| Number of phases | 3 |
| Rated Voltage range [V] | 380-440 |
| Nominal Voltage [V] | 400 |
| Rated frequency [Hz] | 50-60 |
| Current at nominal voltage [A] | 9.5 |
| Current at min rated voltage [A] | 10.0 |
| Current at max rated voltage [A] | 8.6 |
| Recommended supply fuse class | B |
| Recommended RCCB class | A |
| Supply cable area | 4x1,5 mm ² |
| Supply cable length [m] | 3 |
| Typical Supply Connector | GCE16 |
| Standby Power Consumption [W] | <5 |
| Power Consumption [W] | 6247 |
| Apparent Power Consumption [VA] | 6576 |
| Power Factor | 0,95 |
| Leakage current [mA] | <3,5 |
| Efficiency (at rated power and no cables) [%] | 93 |

OUTPUT DATA

| | |
|----------------------------------|-------------------------|
| Output Voltage [V] | 48 |
| Output Current [A] | 100 |
| Output cable cross-section | 35 mm ² |
| Output cable length [m] | 3 |
| Output cable terminals (in unit) | M6 |
| Typical Output connector | DIN160 |
| Output fuse, rating [A/VDC] | 150A/150VDC |
| Output fuse type | Fast Semiconductor fuse |

PROPERTIES

| | |
|--|---------------------|
| Ingress protection | IP20 |
| Ambient temperature range (at full output power) [deg C] | -5 to +40 |
| Ambient max temp (with reduced output power) [deg C] | 50 |
| Ambient storage and transport temperature [C] | -40 to +80/1000h |
| Maximum operating altitude [m] | 2000 |
| Maximum humidity, non-condensing [%rh] | 90 |
| Cabinet Type | S16 |
| Certifications | CE |
| Cloud connection | No |
| Charging Curve Set | 10-04,06,18 & 20-09 |
| I/O-cards | No |
| Reporting | No |
| Radio communication | No |

CHARGER DIMENSIONS

| | |
|--------------------------|-------------|
| Weight excl. cables [kg] | 6.7 |
| Charger dimensions [mm] | 387x266x152 |

SHIPPING DIMENSIONS

| | |
|----------------------|-------------|
| Box dimensions [mm] | 260x325x550 |
| Shipping Weight [kg] | 10.9 |

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.